



An Australian Government Initiative




Biomass energy production in Australia

Status, costs and opportunities for major
technologies

A report for the Joint Venture Agroforestry Program
(in conjunction with the Australian Greenhouse Office)

by C.R. Stucley, S.M. Schuck, R.E.H. Sims,
P.L. Larsen, N.D. Turvey and B.E. Marino

RIRDC Publication No 04/031
RIRDC Project No EPL-1A





An Australian Government Initiative



Biomass energy production in Australia

**Status, costs and opportunities
for major technologies**

**A report for the RIRDC/ FWPRDC
L & W Australia/ MDBC
Joint Venture Agroforestry Program
(in conjunction with the Australian
Greenhouse Office)**

by C.R. Stucley, S.M. Schuck,
R.E.H. Sims, P.L. Larsen,
N.D. Turvey and B.E. Marino

February 2004
RIRDC Publication No 04/031
RIRDC Project No EPL-1A

© 2004 Rural Industries Research and Development Corporation.
All rights reserved.

ISBN 0 642 58741 8
ISSN 1440-6845

'Biomass energy production in Australia: Status, costs and opportunities for major technologies'

Publication No. 04/031

Project No EPL-1A

The views expressed and the conclusions reached in this publication are those of the authors and not necessarily those of persons consulted. RIRDC shall not be responsible in any way whatsoever to any person who relies in whole or in part on the contents of this report.

This publication is copyright. However, RIRDC encourages wide dissemination of its research, providing the Corporation is clearly acknowledged. For any other enquiries concerning reproduction, contact the Publications Manager on phone 02 6272 3186.

Researcher Contact Details

C.R. Stucley* and B.E. Marino
Enecon Pty Ltd
Level 2, 35 Whitehorse Rd
Deepdene, Vic. 3103 Australia

Phone: 03 9817 6255
Fax: 03 9817 6455
Email: cstucley@enecon.com.au

* *Principal Contact*

Prof. R.E.H. Sims
Institute of Technology and Engineering
Massey University
Palmerston North, New Zealand

Dr S.M. Schuck
Stephen Schuck & Associates
7 Grassmere Rd
Killara, NSW 2071 Australia

Dr P.L. Larsen and Dr N.D. Turvey
Greenfield Resource Options Pty Ltd
Unit 10, 43 Lang Pde
Milton, Qld 4064 Australia

In submitting this report, the researcher has agreed to RIRDC publishing this material in its edited form.

RIRDC Contact Details

Rural Industries Research and Development Corporation
Level 1, AMA House
42 Macquarie Street
BARTON ACT 2600
PO Box 4776
KINGSTON ACT 2604

Phone: 02 6272 4819
Fax: 02 6272 5877
Email: rirdc@rirdc.gov.au
Website: <http://www.rirdc.gov.au>

Published in February 2004
Printed on environmentally friendly paper by Canprint

Foreword

There is growing appreciation across much of rural Australia of the benefits that may be realised from increasing tree cover on farms, while still maintaining existing farming activities such as cropping and livestock production. Increased tree cover offers multiple benefits that will vary from location to location. These benefits can be significant and may include:

- environmental improvements, such as salinity, water quality and soil protection
- protection of biodiversity and remnant vegetation
- commercial opportunities for farmers to use farm forestry as an additional income stream.

Benefits may be both on-farm and off-farm. Flow on benefits include greater opportunities for sustainable agricultural practices, diversity of income streams for farmers, protection of rural infrastructure, and a generally improved outlook for Australia's rural communities.

While environmental and social benefits are admirable reasons for tree planting, farm forestry has a greater chance of adoption if it includes commercial returns for farmers. However there are large parts of Australia that do not have the necessary rainfall or proximity to coastal markets and ports to compete with existing plantations of softwoods, or with eucalypts such as blue gum. New products from wood are needed if these inland, low rainfall areas are to reap significant benefits from farm forestry. While any new industry will offer returns to the growers that supply it with wood, products that require large quantities of wood will catalyse tree planting on a scale that many agree is needed to offer a substantive solution to major issues such as salinity.

In the search for large, new industries that could utilise wood as feedstock, particular attention is being paid to renewable energies. Not only does renewable electricity offer its own environmental benefits, it also offers the potential of large markets for sustainably-grown trees across many parts of Australia.

This project was jointly funded by the Joint Venture Agroforestry Program (JVAP) and the Australian Greenhouse Office. JVAP is in turn supported by three R&D Corporations — Rural Industries Research and Development Corporation, (RIRDC), Land & Water Australia and Forest and Wood Products Research and Development Corporation (FWPRDC), together with the Murray-Darling Basin Commission (MDBC). These agencies are principally funded by the Federal Government.

This report, a new addition to RIRDC's diverse range of over 1000 research publications, forms part of our Agroforestry and Farm Forestry R&D program, which aims to integrate sustainable and productive agroforestry within Australian farming systems.

Most of our publications are available for viewing, downloading or purchasing online through our website:

- downloads at www.rirc.gov.au/fullreports/index.htm
- purchases at www.rirc.gov.au/eshop

Simon Hearn

Managing Director

Rural Industries Research and Development Corporation

Acknowledgments

Funding of this study by the Joint Venture Agroforestry Program and the Australian Greenhouse Office is gratefully acknowledged.

A number of individuals have generously provided assistance to the report team. Particular thanks go to Dr Roslyn Prinsley of RIRDC, who assisted in development of the study and its concepts, and in the arrangements for co-funding of the work.

Authors' Disclaimer

This report has been prepared to assist with the appraisal of technologies and costs for projects involving energy from biomass. While every care has been taken in its preparation, the study work and report are preliminary only and no responsibility will be taken by the authors for omissions or inaccuracies, or for the use of this information by any other party.

Contents

Foreword	iii
Acknowledgments	iv
Authors' Disclaimer	iv
Executive Summary	xii
1. Introduction - Biomass to Energy	1
1.1 Summary	1
1.2 Background to Study	1
1.3 So what is Biomass?	2
1.4 Biomass Fuels	5
1.5 Biomass for Renewable Energy and Greenhouse Gas Mitigation	6
1.6 So what is Bioenergy?	7
2. Thermal Properties of Biomass Feedstocks	10
2.1 Summary	10
2.2 Biomass as a Fuel	11
2.3 Determinants of Fuel Properties	12
2.4 Guiding Values for Biomass Fuels	17
2.5 Australian Experience and Capability with Biomass Fuels	18
3. The Harvesting System and Biomass Supply Chain	19
3.1 Summary	19
3.2 Introduction	20
3.3 Harvester Size and Design	23
3.4 Harvester Capacity and Productivity	24
3.5 Width of Cut	25
3.6 Cutting Mechanisms	26
3.7 Comminution	28
3.8 Transfer Mechanism from Harvester	29
3.9 Transport from Field to Storage	30
3.10 Vehicles for Transport to Conversion Plant	31
3.11 Storage	34
3.12 Drying the Biomass	36
4. Harvesting Specific Feedstocks	38
4.1 Summary	38
4.2 Conventional Forestry Harvesting	39
4.3 Short Cycle Crop (SCC) Harvesting Technology	45
4.4 Agricultural Residues	60
4.5 Energy Crops	69
5. Biomass - Delivered Costs	71
5.1 Summary	71
5.2 Introduction	72
5.3 System Options	73
5.4 Supply System for Mallee Eucalypts	74
5.5 The Overall Biomass Supply System	79
5.6 Analysis of Short Cycle Willow Crops Under British Conditions.	83

5.7	Study Methodology	89
5.8	Assessment of SCC Harvesting and Fuel Supply System Costs	90
5.9	Study Recommendations	96
5.10	Further Reading	99
6.	Energy Technologies – Electricity and Heat	100
6.1	Summary	100
6.2	Introduction	101
6.3	Combustion	102
6.4	Gasification	106
6.5	Pyrolysis	109
7.	Secondary Energy Conversion Technologies	120
7.1	Summary	120
7.2	Introduction	121
7.3	Internal Combustion Engines	122
7.4	Steam Turbines	123
7.5	Steam Engines	125
7.6	Co-firing	125
7.7	Emerging Technologies	129
7.8	Indirectly Fired Gas Turbines	131
7.9	Directly Fired Pressurised Gas Turbines	132
7.10	Micro-turbines	132
7.11	Advanced Combined Cycle Gasification Technologies	133
7.12	Conversion of Pyrolysis Bio-oil	136
7.13	Fuel Cells	137
7.14	Discussion	139
8.	Energy Technologies – Ethanol	140
8.1	Summary	140
8.2	Introduction	141
8.3	Sulphuric Acid Technologies	142
8.4	Other Technologies	151
8.5	Costs of Production	152
8.6	Future Developments	154
8.7	Co-production of Electricity	156
8.8	Discussion	156
9.	Energy Technologies – Methanol	160
9.1	Summary	160
9.2	Introduction	161
9.3	Methanol from Biomass	162
9.4	Engineering and Costing Studies	164
9.5	Methanol from Dual Feeds	165
9.6	Co-production of Electricity	165
10.	Costs for Electricity	166
10.1	Summary	166
10.2	Introduction	167
10.3	Capital Costs	168
10.4	Operating Costs	169
10.5	Costing Model	170
10.6	Price of Electricity	170
10.7	Electricity - Sensitivity Analysis	171
10.8	Discussion	176

11. Plant Costs - Liquid Fuels	177
11.1 Summary	177
11.2 Estimated Costs	178
12. The Project Development Pathway	181
12.1 Summary	181
12.2 Introduction	181
12.3 Selecting Technology	182
12.4 Staged Development	183
13. Case Studies – Production of Biomass	187
13.1 Summary	187
13.2 Background	188
13.3 Locations	189
13.4 Climate	189
13.5 Land suitability	192
13.6 Infrastructure	193
13.7 Biomass Productivity	193
13.8 Growing Biomass for Renewable Energy	195
13.9 Biomass from Short Cycle Crops	195
13.10 Short Cycle Crops SEQ	196
13.11 Short Cycle Crops MDB	198
13.12 Biomass from Tree Plantation Crops	201
13.13 Comparison of Biomass Costs	206
14. Case Studies – Harvest and Transport	207
14.1 Summary	207
14.2 Transport of the Biomass to a Conversion Plant	207
14.3 Model Assumptions	209
14.4 Results	211
14.5 Conclusions	215
14.6 Further Reading	215
15. Case Studies – Production of Electricity	217
15.1 Background	217
15.2 Economic Analysis	217
16. Co-products and Co-values	223
16.1 Summary	223
16.2 Introduction	225
16.3 Co-Values from Bioenergy	227
16.4 Co-Products	234
17. Attachments	242
17.1 Attachment 1 - Glossary and Abbreviations	243
17.2 Attachment 2 - Bioenergy Related Units	245
17.3 Attachment 3 - Standardisation of Capital Costs	248

List of Figures

Figure 1-1:	The Earth's energy flows are in balance	4
Figure 1-2:	An indication of the relative scales of energy conversion plants using biomass fuels and a comparison with fossil fuel power plants	5
Figure 1-3:	Some routes for converting a number of different biomass materials into useful energy products	8
Figure 2-1:	Van Krevelen Diagram for Solid Fuels	12
Figure 2-2:	Elemental Composition of Typical Biomass Fuels	14
Figure 2-3:	Nitrogen, Sulphur and Chlorine Compositions of Biomass Feedstocks	14
Figure 2-4:	Variation of heating values with moisture content for typical biomass fuel	16
Figure 2-5:	Bulk Densities of Various Biomass Fuels	16
Figure 2-6:	Guiding Values for Unproblematic Utilisation of Biomass Fuels	18
Figure 3-1:	Whole eucalyptus trees harvested at 3 years old and stored ready for processing	21
Figure 3-2:	Self-propelled Swedish prototype harvester on tracks	23
Figure 3-3:	Prototype willow harvester from Ireland cutting a double row in one pass	26
Figure 3-4:	Close up of one type of design of feller cutting head	27
Figure 3-5:	Chips being blown into a trailed bin	30
Figure 3-6:	Forwarder in Sweden with grapple and trailer	31
Figure 3-7:	European example - Unloading straw bales by tractor front loader	32
Figure 3-8:	Bales of willow sticks formed by a prototype Swedish Balapress under test in UK.	33
Figure 4-1:	Forwarder tractor or forestry logging trailer with hydraulic loading boom and grapple	40
Figure 4-2:	Specialist forestry forwarder with articulated chassis	40
Figure 4-3:	Cable hauler tower in <i>P. radiata</i> plantation	42
Figure 4-4:	Cable hauler extraction of logs in steep terrain	42
Figure 4-5:	Articulated winch skidder working in poorly managed plantation	43
Figure 4-6:	Grapple processor delimbing, topping and sectioning stemwood to desired lengths	44
Figure 4-7:	Sliding boom processor at landing delimbing logs.	44
Figure 4-8:	Harvesting large or small trees	45
Figure 4-9:	Feller buncher with accumulating head developed for SCC harvesting of poplars in the USA	46
Figure 4-10:	FB7 prototype harvester	46
Figure 4-11:	The Claas forage harvester twin disc cutting head developed to SCC willow	47
Figure 4-12:	Hydroaxe feller buncher harvesting poplars.	48
Figure 4-13:	Growth form difference between Pinus and Eucalyptus species	49
Figure 4-14:	Trailer mounted chipper with auxiliary power supply	56
Figure 4-15:	Tractor mounted chipper for small scale applications	56
Figure 4-16:	Using large mobile chipper to collect and chip <i>P. radiata</i> plantation thinnings	57
Figure 4-17:	Heavy duty chipper handling SCC poplar at around 30 odt/h with grapple feed	57
Figure 4-18:	Drying a two day supply of fuelwood	58
Figure 4-19:	Typical heat losses during combustion	59
Figure 4-20:	Biomass has good potential to provide rural areas with a renewable source of energy	60
Figure 4-21:	Sugar cane billets from the harvester	62
Figure 4-22:	Fibrous bagasse residue after extraction of the sugar	62
Figure 4-23:	Energy and material flows during the sugar cane production and processing operation.	64
Figure 4-24:	Transport of sugar cane from field to factory by small rail and bins	65
Figure 4-25:	Rail bins being filled in the field by the harvester support trailer	65
Figure 4-26:	Open air burning of straw as a disposal method causes air pollution	67
Figure 4-27:	An example of one of many models of straw-fired burners	67
Figure 4-28:	A range of commercially produced straw pellet types and sizes	68

Figure 4-29:	Oilseed crop growing in Manawatu, New Zealand.....	69
Figure 4-30:	Typical lower heating values for some vegetable oils and diesel	70
Figure 5-1:	Range of typical systems used for harvesting, collecting and processing biomass.....	74
Figure 5-2:	Feed cost model, including typical values for each variable.....	78
Figure 5-3:	Costs of delivered fuel from forest arisings from seven different systems.	79
Figure 5-4:	A comparison of delivered costs of a tonne of oven dry fuelwood.....	81
Figure 5-5:	Billets of willow stock-piled on farm.....	84
Figure 5-6:	Tractor powered stick harvester suitable for small scale harvesting	85
Figure 5-7:	Large square straw bales stored at the power plant ready for use	87
Figure 5-8:	Bagasse baled and stored for use in a sugar processing co-generation plant during the non-cane crushing season.....	88
Figure 5-9:	Chips being delivered to a Canadian wood-fired power plant by tipping truck.....	88
Figure 5-10:	Transport of round bales on heavy goods vehicle and trailer.....	91
Figure 5-11:	Round bales fed into shredder on automatic conveyor to feed straw burner	92
Figure 5-12:	Straw bale being dropped into shredder to feed combustion plant	93
Figure 5-13:	Willow stick harvester with collection platform to accumulate load till drop off when full.	94
Figure 5-14:	Key assumptions of machine costs and performance rates used in the base case models....	95
Figure 5-15:	Whole bale burner under development in Denmark.	97
Figure 6-1:	Primary and secondary conversion technologies suited to biomass projects.	102
Figure 6-2:	Heat Plant.....	103
Figure 6-3:	Co-generation Plant.....	105
Figure 6-4:	Gasification Plant	106
Figure 6-5:	Illustrative designs of gasification reactor designs showing areas of chemical activity and typical temperatures.....	109
Figure 6-6:	Pyrolysis Plant.....	109
Figure 6-7:	Pyrolysis Products and Applications.....	110
Figure 6-8:	Products of Slow and Fast Pyrolysis.....	110
Figure 6-9:	Conceptual Fluidised Bed Pyrolysis Process	113
Figure 6-10:	Typical properties and characteristics of wood derived bio-oils.....	114
Figure 6-11:	Typical Properties of Bio-oil Compared to Diesel Fuel.....	115
Figure 7-1:	Small scale batch fed gasifier fueling Internal Combustion Engine	123
Figure 7-2:	Power Plant	123
Figure 7-3:	Steam turbine driving a 25 MW _e generator in a wood-fired power plant in Canada	124
Figure 7-4:	The Stirling engine uses a closed thermodynamic cycle.....	130
Figure 7-5:	BIGCC Plant	133
Figure 7-6:	The Yorkshire Arbre process for a willow coppice and wood process residue fuelled gasification combined-cycle plant.....	135
Figure 7-7:	Applications of pyrolysis bio-oil.....	136
Figure 7-8:	Operating principle of a fuel cell.....	138
Figure 8-1:	Summary of Major Technology Providers.....	150
Figure 8-2:	Ethanol Plant Costs - Molasses Feed	152
Figure 8-3:	Ethanol Price Break-down - Molasses Feed.....	153
Figure 8-4:	Summary of Projected Improvements in Ethanol Processing	155
Figure 9-1:	Composition of dry synthesis gas produced by different biomass gasifiers	163

Figure 10-1: Assessment of costs per year.....	166
Figure 10-2 Electricity Price as a function of Plant Capacity.....	167
Figure 10-3: Electricity Plant Parameters	168
Figure 10-4: Breakdown of Capital Costs.....	168
Figure 10-5: Breakdown of Operating Costs	169
Figure 10-6: Labour Cost Breakdown.....	169
Figure 10-7: Assumptions Used for the Economic Analysis of Bioenergy Systems.....	170
Figure 10-8: Results of Economic Analysis.....	170
Figure 10-9: Electricity Price Breakdown.....	171
Figure 10-10: Power Price Variation due to Feed Cost Changes.....	172
Figure 10-11: Power Price Variation due to Plant Utilisation Changes.....	173
Figure 10-12: Power Price Variation due to Capital Cost Changes	174
Figure 10-13: Power Price Variation due to Operation and Maintenance Cost Changes	175
Figure 10-14: Power Price Variation due to Equity Portion of Capital Changes	175
 Figure 11-1: Ethanol Project Cost Parameters	177
Figure 11-2: Methanol Project Cost Parameters	177
Figure 11-3: Ethanol Project Cost Parameters	178
Figure 11-4: Methanol Project Cost Parameters	179
Figure 11-5: Project Financial Assumptions.....	180
 Figure 13-1: Average climate data for typical sub-tropical location in SE Queensland.....	189
Figure 13-2: Monthly rainfall for a sub-tropical location in SEQ	190
Figure 13-3: Probability of not harvesting over the year for plantation crops grown in SEQ	190
Figure 13-4: Average climate data for typical temperate location in MDB.....	191
Figure 13-5: Monthly rainfall for a temperate location in the MDB	191
Figure 13-6: Probability of not harvesting in a year for the MDB.....	192
Figure 13-7: Land suitability classes for biomass production.....	192
Figure 13-8: Infrastructure and Land Suitability Class within 25, 50, 75 and 100 km arcs of the bioenergy conversion plant for each site.....	193
Figure 13-9: Potential biomass production rates in SEQ and MDB.	194
Figure 13-10: Assumptions assessing the economics of short cycle crops in SEQ and MDB.	195
Figure 13-11: Sensitivity analysis of stumpage price for biomass grown in SCC in SEQ	196
Figure 13-12: Area required to supply an average of 300,000 t FW p.a. from SCC in SEQ.....	197
Figure 13-13: Area required to supply an average of 700,000 t FW p.a. from SCC in SEQ.....	197
Figure 13-14: Sensitivity analysis of stumpage price for biomass grown in SCC in MDB.....	198
Figure 13-15: Area of land required to be established to supply 300,000 t FW p.a. to a renewable energy plant in the MDB.....	199
Figure 13-16: Area of land required to be established to supply 700,000 t FW per annum to a renewable energy plant in the MDB.	200
Figure 13-17: Assumptions used to assess the economics of using biomass from tree plantation crops in SEQ and MDB	201
Figure 13-18: Product table for tree plantation crops grown in SEQ and MDB.....	202
Figure 13-19: Sensitivity analysis of price for biomass grown in TPC in SEQ.....	202
Figure 13-20: Quantity of biomass produced from first and second thinning and clearfall harvest of TPC in SEQ that is available for bioenergy production.	203
Figure 13-21: Sensitivity analysis of price for biomass grown in TPC in MD.....	204
Figure 13-22: Quantity of biomass harvested from first and second thinning and clearfall harvest of TPC in MDB that is available for bioenergy production.	205
Figure 13-23: Comparison of the price paid for biomass produced in SCC and TPC production systems in SEQ and MDB.....	206

Figure 14-1: Overview of locations, feedstocks and system options	208
Figure 14-2: Alternative Harvest and Transport Systems	209
Figure 14-3: Delivered costs of biomass from short cycle crops	213
Figure 14-4: Sensitivity analysis for delivered costs	214
Figure 14-5: Base case assumptions used for moisture contents and dry matter losses.....	214
Figure 15-1: Assumptions Used for the Economic Analyses	217
Figure 15-2: Key Parameters for Case Study Options	218
Figure 15-3: Results of Economic Analysis.....	219
Figure 15-4: Electricity Price Breakdown for Power Plants Located in South-East Queensland.....	219
Figure 15-5: Electricity Price Breakdown for Power Plants located in the Murray Darling Basin	220
Figure 15-6: Impact of Feed Cost on Electricity Price.....	221
Figure 15-7: Impact of Capital Cost on Electricity Price.....	222
Figure 16-1: Life Cycle Carbon Dioxide Equivalent Emissions for various technologies (g/kWh)	228
Figure 16-2: Annual costs due to water tables/salinity (\$m) in Western Australia	229
Figure 16-3: Concept and Products from a Bio-Refinery	239
Figure 17-1: Large compacted briquettes of around 1kg each , produced from shredded whole trees...	246

Executive Summary

This report examines the use of biomass to generate electricity and produce liquid transport fuels. There are many different forms of biomass, from forestry and agriculture and from a range of process industries. The main focus of this study is on biomass from forestry, particularly new forestry that may also achieve other environmental benefits in Australia's dryland regions.

The report is generally structured as follows:

a) Biomass is discussed first, including:

- Its properties and characteristics with respect to bioenergy
- The components and variables in the supply chain for harvesting biomass and transporting it to bioenergy plants
- Experience with specific feedstocks
- Costs of delivery for specific feedstocks.

With an emphasis on new tree planting in this study, examples of several short cycle tree crops are provided. Growing and harvesting short cycle mallee eucalypts in Australia is already reported by RIRDC ¹, and the authors are not aware of other published work on short cycle forestry in Australia. This study has therefore used overseas experience for much of its discussion of biomass harvesting and transportation.

- b) Technical sections are then provided to introduce current and projected technologies for production of electricity and liquid fuels from biomass feedstocks.
- c) Following the technical sections is a summary of costs for several hypothetical examples of electricity and alcohol fuel plants, as well as overall costing of bioenergy systems and a preliminary sensitivity analysis.
- d) With a view to understanding opportunities for new tree planting in Australia, case studies have been developed that examine short cycle (tree) crops for bioenergy and also for more conventional long rotation plantations. Locations examined are in south east Queensland and the Murray Darling Basin.
- e) The work undertaken for the study showed that in many cases bioenergy alone is not a viable commercial driver for the new tree planting that the Joint Venture Agroforestry Project (JVAP) is encouraging across much of Australia. The report therefore examines other products that may be possible if biomass supplies are established for a bioenergy industry. Also considered are the other environmental and social benefits that would result from new tree planting and bioenergy in rural areas.

¹ Integrated Tree Processing of Mallee Eucalypts. www.rirdc.gov.au/reports/AFT/01-160sum.html

1. Introduction - Biomass to Energy

1.1 Summary

Biomass is organic matter originally derived from plants, produced through the process of photosynthesis, and which is not fossilised (such as coal). Biomass can act as a store of chemical energy to provide heat, electricity and transportation fuels, or as a chemical feedstock for bio-based products.

Biomass resources include wood from plantation forests, residues from agricultural and forest production, and organic waste streams from industry, livestock, food production, and general human activities. Examples are wood chips, sawdust, cotton ginning trash, nut shells, manure and human sewage. This study has focused principally on biomass from trees and then agricultural crops. Other sources of biomass, such as animal and human wastes, are not considered here.

Biomass for energy is a unique form of renewable, solar energy. Of the massive $178,000 \times 10^{12}$ Watts of solar energy that falls on the Earth's surface, some 0.02% or 40×10^{12} Watts is captured by plants via photosynthesis and bound into biomass energy. This translates into the production of some 220 billion 'dry' tonnes of biomass per year, which as an energy source represents some ten times the world's total current energy use. Currently some 15 percent of the planet's energy requirements are met from biomass, mainly for cooking and heating in developing countries, but also increasingly for fuelling a growing number of large scale, modern biomass energy plants in industrialised countries.

Bioenergy is essentially renewable or carbon neutral. Carbon dioxide released during the energy conversion of biomass (such as combustion, gasification, pyrolysis, anaerobic digestion or fermentation) circulates through the biosphere, and is reabsorbed in equivalent stores of biomass through photosynthesis.

Bioenergy plants can range from small domestic heating systems to multi-megawatt industrial plants requiring several hundred thousand tonnes of biomass fuel per annum each. There are also a variety of technologies to release and use the energy contained in biomass, such as combustion technologies that are well proven and widely used world-wide, and more efficient gasification plants that are currently at the demonstration stage but with potential for significant cost reduction as the technology is commercialised in multiple plants.

1.2 Background to Study

The Joint Venture Agroforestry Program (JVAP) was established in 1993 to foster agroforestry research and development. It is managed by the Rural Industries R&D Corporation on behalf of that organisation as well as the Land & Water Australia, the Forest and Wood Products R&D Corporation and the Murray Darling Basin Commission.

In response to the urgent need to develop new commercially driven tree production systems to manage dryland salinity, the program's highest priorities are:

- to develop new tree products;
- to redesign agricultural systems to incorporate woody perennials for medium to low rainfall areas.

The introductory paragraphs of two recent publications by JVAP provide a summary of the situation:

“The replacement of native vegetation with crops and pastures that use less water has resulted in rising groundwater levels, causing salinity damage over wide and growing areas. The problem can be alleviated by tree planting, but this requires careful planning based on knowledge of the affected catchment”¹.

“Farm forestry is important to Australia’s sustainable natural resource management. Tree planting has particular environmental rewards in areas with low to medium rainfall (400 – 700). Unless trees are profitable for farmers in these areas they will never be planted on a sufficient scale to achieve desired environmental benefits”².

The dryland agricultural regions that are already affected by salinity, or are susceptible to future salinity damage, cover much of the Western Australian wheat belt and also large parts of the Murray Darling Basin. Together they represent many millions of hectares that are either already damaged or are expected to be damaged if nothing is done. Commercial returns for biomass will catalyse tree planting by farmers. Each project to commercialise tree planting in an area can be of benefit to that area. However, solutions that can be seen to catalyse tree planting on a large or regional scale are of particular interest to groups such as JVAP.

Bioenergy, either as electricity or as liquid fuels, represents a huge potential market for new tree plantings. As such, bioenergy is of considerable interest to JVAP. The renewable nature of such energy is also of interest to the Australian Greenhouse Office as a potential method for large scale reduction of carbon dioxide emissions in Australia.

The extremely varied nature of biomass, and the many routes possible for converting the resource to bioenergy, makes the whole topic of biomass to energy a complex subject. For energy from wind, solar and hydro the conversion technology is the key component, whereas for biomass the whole system needs to be included. This entails gaining an understanding of the range of diverse biomass resources; how to cost-effectively process and deliver these resources in a useful form to the conversion plant; how biomass can be transformed into heat, electricity, or both in a co-generation plant, or how biofuels can be used for transport fuels. The use of biomass for building and construction materials (to displace the higher energy-containing steel, aluminium or concrete) or as a chemical feedstock (as a substitute for petro-chemicals) is largely beyond the focus of this report.

1.3 So what is Biomass?

From a renewable energy perspective, biomass can be defined as:

Recent organic matter originally derived from plants as a result of the photosynthetic conversion process or from animals and which is destined to be utilised as a store of chemical energy to provide heat, electricity, or transport fuels.


Biomass resources include wood from plantation forests, residues from agricultural or forest production, and organic waste by-products from industry, domesticated animals, and human activities.

The chemical energy contained in the biomass is derived from solar energy using the process of photosynthesis. (Photo means to do with light and synthesis is the putting together). This is the process by which plants take in carbon dioxide and water from their surroundings and, using energy from sunlight, convert them into sugars, starches, cellulose, lignin etc which make up vegetable

¹ Trees, Water & Salt: An Australian guide to using trees for healthy catchments and productive farms – The JVAP Research Update Series No. 1, October 2000

² Emerging products and services from trees in lower rainfall areas - The JVAP Research Update Series No. 2, October 2000

matter loosely termed carbohydrates (and shown for simplicity as [CH₂O]). Oxygen is produced and emitted.



All plant matter on Earth, both terrestrial and marine, is formed using this process. Animals that consume plant material and even carnivorous species all depend directly or indirectly on photosynthesis. Thus many animal products and wastes can also be classified as forms of biomass if used for energy purposes. Only a very small portion of the solar radiation reaching the Earth is used for photosynthesis (Figure 1-1).

World-wide, photosynthesis produces approximately 220 billion tonnes (dry weight) of biomass per year. As an energy source, this represents some ten times the world's current energy use. Globally around 55EJ/year of biomass is currently used for energy purposes, mainly for cooking and heating in developing countries, but also for running a growing number of large scale modern biomass energy plants. This is some 15 percent of the world's energy use. By comparison the world population consumes around 10EJ/year of energy in the form of food, which of course is a biomass energy resource in itself.

1.4 Biomass Fuels

Fuels resulting from biomass may be any solid, liquid or gaseous fuel produced from a wide range of organic raw materials, either directly from plants or indirectly from industrial, commercial, domestic, forest or agricultural wastes and produced in a variety of ways. These cover a very wide range of energy sources and scales (Figure 1-2), from simple firewood for small domestic fires to 500,000 tonnes of sugar cane residue (bagasse) a year used to fire a 50MW co-generation plant at a sugar mill.

Size	Properties served	Annual fuel demand	Vehicle movements	Conversion technology	Physical size	Investment cost
Domestic heating (15kWt)	Family dwelling	3 - 5 odt wood	2 - 3 tractor loads /y	Boiler or wood burner	Large suitcase	\$ 100s
Small business heating (350kWt)	School or small factory	80 – 120 odt wood or straw	40 tractor loads /y	Boiler or straw burner and fans	Garage for one car	\$ 10,000s
Small electricity generating plant (250kWe)	200 – 300 houses or small industry	1500 – 2000 odt wood or straw or wet wastes	6 x 20t trucks / week	IC* engine or gasifier	Small barn	\$ 10,000s
Medium electricity generating plant (5MWe)	4000-6000 houses or small industrial estate	20 – 30,000 odt of range of biomass fuels	50 x 38t trucks / week	IC engine or steam turbine or gasifier	Petrol service station	\$100,000s
Large electricity generating plant (30MWe)	25-35000 house or industrial estate	120-140,000 odt using dry biomass fuels	250 x 38t trucks / week	Steam turbine or gas turbine or combined cycle	Large church	\$ millions
Combined cycle gas turbine or coal-fired station (500MWe)	500,000 houses or large industrial site	800 Mm3 gas or 1Mt coal	Pipeline Or 900 x 38t trucks / week equiv	Gas turbine and / or steam turbine	Large barn or Sydney Opera House	\$ millions

*IC = internal combustion engine

Figure 1-2: An indication of the relative scales of energy conversion plants using biomass fuels and a comparison with fossil fuel power plants

[Source: Wood Fuel from Forestry and Arboriculture, Department of Trade and Industry & ETSU, July 1999].


The larger the project then usually the less the investment cost in terms of \$/MW installed capacity. If the biomass is already collected on site, as in the case of wood process residues from a sawmill, then the size of bioenergy plant is usually limited by that available resource. Where the biomass is brought into a central plant location, the transport distance and corresponding cost will be a limiting factor to the commercially viable size of bioenergy plant.

Whilst they are not considered in any detail in this report, waste-to-energy processes are also included under the general term “biomass” as they mainly consist of what were originally plant or animal products derived from their use for purposes other than for energy (e.g. paper, packaging, pallets). Urban, commercial and industrial wastes, sometimes classed as municipal solid wastes, can have the inorganic and non-combustible fractions (e.g. glass and metal) removed, leaving mainly waste of biological origin – apart from the plastic component which is fossil fuel derived but also combustible.

Combustion of fuel with atmospheric oxygen provides energy as heat. Natural decomposition of biomass is a similar oxidation process, but the chemical energy is released as heat much more slowly. Both processes produce carbon dioxide and water. But that is not the end of the process, as nature completes the cycle putting energy (from the sun) back into these end-products via growing plants to create more fuel and oxygen.

Some materials will burn and others, such as sand and water, will not. Combustion of a fuel needs oxygen to chemically react the carbon and hydrogen containing molecules of the fuel. Heat is produced. Therefore a fuel can be defined as a substance which interacts with oxygen, changes chemically, and thereby releases its stored chemical energy.

For example, methane (CH₄), a common fuel as contained in natural gas, biogas, or landfill gas, reacts with oxygen (O₂) as follows:



This chemical reaction typifies the burning of any common fuel: a compound containing carbon and hydrogen interacts with oxygen (usually from the air though there are cases when pure oxygen is used) to produce carbon dioxide and water.

Section 2 of this report considers the combustion properties of biomass feedstocks.

1.5 Biomass for Renewable Energy and Greenhouse Gas Mitigation

Scientists are now confident that an enhanced greenhouse effect is occurring and that a substantial part of the observed change in climate is due to human activities. Fossil fuels are abundant and projections from the World Energy Council suggest that oil, coal and gas should all be available throughout most of this century and that they will remain the dominant energy source for the foreseeable future.

As a response, carbon dioxide emissions to the atmosphere can be reduced by:

- lowering the levels of energy services
- providing energy or consuming energy services via more efficient technologies and systems thereby reducing energy intensity
- switching from fossil fuels to renewable sources of energy, including biomass, or to nuclear energy, or switching from higher carbon fuels (coal) to lower carbon fuels (gas)
- removing carbon from fuels and combustion exhaust gases or from the atmosphere and storing it in some way in perpetuity (sequestration).

Biomass is a renewable energy resource that results in a negligible net contribution of CO₂ to the atmosphere. Plants during growth take up CO₂ which is later released during bioenergy processes.

Where agricultural land is transferred to energy crop production, a net uptake of CO₂ also often results from the increased ‘carbon density’ of the land use and possibly in the soil too. Other forms of biomass utilisation such as landfill gas or the collection of forest residues otherwise left to decompose on the forest floor, also reduce the release of methane (a more potent greenhouse gas) into the atmosphere.

Biomass has the dual advantage of acting as an energy substitute for fossil fuels (a carbon offset) and also as a means of sequestering carbon (a carbon sink). Hence it is recognised widely that bioenergy will play an important role in the objectives of the United Nations Framework Convention on Climate Change (UNFCCC). An excerpt from the International Energy Agency Bioenergy News from 1998 best sums up the potential of using bioenergy.

Modern bioenergy options offer significant, cost-effective and perpetual opportunities toward meeting emission-reduction targets while providing ancillary benefits. Moreover, via the sustainable use of the accumulated carbon, bioenergy has the potential for resolving some of the critical issues surrounding the long-term maintenance of biotic carbon stocks. Finally, wood products can act as substitutes for more energy-intensive products, can constitute carbon sinks, and can be used as biofuels at the end of their lifetime¹.

CO₂ emissions can be reduced by approximately 97% and 93% where suitable biomass is combusted for electricity generation and substitutes for coal or gas respectively. However, the use of more efficient bioenergy conversion systems such as gasification, can further improve emission reductions.

1.6 So what is Bioenergy?

A number of conversion routes exist to change biomass into useful forms of energy, as shown in simplified form in

Figure 1-3. Many of these will be covered in detail in later sections of this report. The owner of a biomass resource can work in partnership with a project developer to convert that resource into useful energy projects in order to maximise the return on the investment. Where the resource is a waste product, avoiding any treatment or disposal costs can lead to dual benefits, or a “win/win” opportunity.

The biomass conversion routes can determine whether or not a project is commercially viable and the costs for these conversion processes are often very site and project specific. They vary with the source of raw biomass, its moisture content, the transport distance, the complexity of the process involved, the plant scale, the value of any co-products, the savings of disposal cost if a waste, the reduction in greenhouse gas emissions, the market value for the bioenergy, and whether there are subsidies and incentives available. Careful analysis and risk assessment are therefore required to get a good overview of what is involved and the chance of commercial success for each project.

Costs for many bioenergy plant options can be determined by working with experienced technologists or equipment suppliers, and the more accurate the data provided, the more accurate will be the estimates of project costs.

Over time it is expected that bioenergy project costs will reduce as industry knowledge increases with regard to feed materials, technical alternatives for processing, and operating characteristics. It is possible to learn from projects already in place. As for any technology, bioenergy plants should progress steadily down the experience curve as a result of “learning by doing”. In rough terms the installed cost of a plant will reduce by 20% for every doubling of the total installed capacity. Some bioenergy technologies such as wood combustion are relatively mature (though some increased

¹ IEA, 1998

efficiencies are still being gained for little extra investment costs). Others, such as aspects of wood gasification, are still at the demonstration stage with potential for rapid cost reduction when replication occurs.

This report examines in some detail the elements of bioenergy, from the nature of biomass as a fuel source, issues related to its production, harvesting and transport, its conversion into primary and secondary energy products and services, costs and economics of bioenergy in its various forms, and co-values and co-products associated with bioenergy.




Figure 1-3: Some routes for converting a number of different biomass materials into useful energy products

A note on Terminology

During the course of the study several different names were identified for groups of trees that would be harvested regularly in cycles of several years, as opposed to the cycle times of fifteen years or more. The latter times typically apply to plantations established for sawlogs or processing for other wood products. In defining these short cycle trees attention was given to whether the tree:

- is to be harvested in short “rotation” or short “cycle”. In forestry the two terms are similar, however in agriculture rotation can be taken to mean a change of crop rather than a time for growth.
- is planted for energy alone or for energy and other uses. Unless the usage is specifically for energy for illustrative purposes (for example in the Australian case studies developed as part of this project) we have endeavoured to avoid the use of “energy”, to promote the concept that crops planted for multiple products or purposes are more likely to be commercially viable than trees planted for energy alone.
- coppices (resprouts from the cut base after harvesting). We have endeavoured to avoid the term “coppice” as some tree species with potential for biomass and other uses do not coppice.
- is part of a plantation, forest or crop. There are no apparent distinctions between each word. We have endeavoured to use “crop” to focus on the difference between these short cycle trees and current use of “plantations” to describe stands of pine and blue gum.

This report therefore uses “short cycle crops” as its preferred terminology but also makes use of other, similar terms where it is felt appropriate.